

TABLE OF CONTENTS

| <u>Section</u> | <u>Title</u> | <u>Page</u> |
|--|---|---------------|
| CHAPTER 15 ACCIDENT ANALYSES..... | | 15.0-1 |
| 15.0.1 | Classification of Plant Conditions..... | 15.0-1 |
| 15.0.1.1 | Condition I: Normal Operation and Operational Transients | 15.0-1 |
| 15.0.1.2 | Condition II: Faults of Moderate Frequency..... | 15.0-2 |
| 15.0.1.3 | Condition III: Infrequent Faults..... | 15.0-3 |
| 15.0.1.4 | Condition IV: Limiting Faults | 15.0-4 |
| 15.0.2 | Optimization of Control Systems | 15.0-5 |
| 15.0.3 | Plant Characteristics and Initial Conditions Assumed in the Accident Analyses | 15.0-5 |
| 15.0.3.1 | Design Plant Conditions | 15.0-5 |
| 15.0.3.2 | Initial Conditions | 15.0-5 |
| 15.0.3.3 | Power Distribution | 15.0-6 |
| 15.0.4 | Reactivity Coefficients Assumed in the Accident Analysis | 15.0-7 |
| 15.0.5 | Rod Cluster Control Assembly Insertion Characteristics | 15.0-7 |
| 15.0.6 | Protection and Safety Monitoring System Setpoints and Time Delays to Trip Assumed in Accident Analyses..... | 15.0-8 |
| 15.0.7 | Instrumentation Drift and Calorimetric Errors, Power Range Neutron Flux..... | 15.0-8 |
| 15.0.8 | Plant Systems and Components Available for Mitigation of Accident Effects..... | 15.0-9 |
| 15.0.9 | Fission Product Inventories..... | 15.0-9 |
| 15.0.10 | Residual Decay Heat..... | 15.0-9 |
| 15.0.10.1 | Total Residual Heat..... | 15.0-9 |
| 15.0.10.2 | Distribution of Decay Heat Following a Loss-of-Coolant Accident..... | 15.0-9 |
| 15.0.11 | Computer Codes Used | 15.0-10 |
| 15.0.11.1 | FACTRAN Computer Code | 15.0-10 |
| 15.0.11.2 | LOFTRAN Computer Code | 15.0-10 |
| 15.0.11.3 | TWINKLE Computer Code | 15.0-11 |
| 15.0.11.4 | VIPRE-01 Computer Code..... | 15.0-12 |
| 15.0.11.5 | COAST Computer Program | 15.0-12 |
| 15.0.12 | Component Failures | 15.0-12 |
| 15.0.12.1 | Active Failures | 15.0-12 |
| 15.0.12.2 | Passive Failures | 15.0-13 |
| 15.0.12.3 | Limiting Single Failures | 15.0-13 |
| 15.0.13 | Operator Actions | 15.0-13 |
| 15.0.14 | Loss of Offsite ac Power | 15.0-13 |
| 15.0.15 | Combined License Information..... | 15.0-14 |
| 15.0.16 | References..... | 15.0-15 |

TABLE OF CONTENTS (Cont.)

| <u>Section</u> | <u>Title</u> | <u>Page</u> |
|----------------|---|-------------|
| 15.1 | Increase in Heat Removal From the Primary System | 15.1-1 |
| 15.1.1 | Feedwater System Malfunctions that Result in a Decrease in Feedwater Temperature | 15.1-1 |
| 15.1.1.1 | Identification of Causes and Accident Description..... | 15.1-1 |
| 15.1.1.2 | Analysis of Effects and Consequences | 15.1-2 |
| 15.1.1.3 | Conclusions | 15.1-2 |
| 15.1.2 | Feedwater System Malfunctions that Result in an Increase in Feedwater Flow..... | 15.1-2 |
| 15.1.2.1 | Identification of Causes and Accident Description..... | 15.1-2 |
| 15.1.2.2 | Analysis of Effects and Consequences | 15.1-3 |
| 15.1.2.3 | Conclusions | 15.1-6 |
| 15.1.3 | Excessive Increase in Secondary Steam Flow..... | 15.1-6 |
| 15.1.3.1 | Identification of Causes and Accident Description..... | 15.1-6 |
| 15.1.3.2 | Analysis of Effects and Consequences | 15.1-7 |
| 15.1.3.3 | Conclusions | 15.1-9 |
| 15.1.4 | Inadvertent Opening of a Steam Generator Relief or Safety Valve..... | 15.1-9 |
| 15.1.4.1 | Identification of Causes and Accident Description..... | 15.1-9 |
| 15.1.4.2 | Analysis of Effects and Consequences | 15.1-10 |
| 15.1.4.3 | Margin to Critical Heat Flux | 15.1-12 |
| 15.1.4.4 | Conclusions | 15.1-12 |
| 15.1.5 | Steam System Piping Failure | 15.1-12 |
| 15.1.5.1 | Identification of Causes and Accident Description..... | 15.1-12 |
| 15.1.5.2 | Analysis of Effects and Consequences | 15.1-14 |
| 15.1.5.3 | Conclusions | 15.1-18 |
| 15.1.5.4 | Radiological Consequences..... | 15.1-18 |
| 15.1.6 | Inadvertent Operation of the PRHR Heat Exchanger..... | 15.1-20 |
| 15.1.6.1 | Identification of Causes and Accident Description..... | 15.1-20 |
| 15.1.6.2 | Analysis of Effects and Consequences | 15.1-21 |
| 15.1.6.3 | Conclusions | 15.1-24 |
| 15.1.7 | Combined License Information..... | 15.1-24 |
| 15.1.8 | References..... | 15.1-24 |
| 15.2 | Decrease in Heat Removal by the Secondary System..... | 15.2-1 |
| 15.2.1 | Steam Pressure Regulator Malfunction or Failure that Results in Decreasing Steam Flow | 15.2-1 |
| 15.2.2 | Loss of External Electrical Load | 15.2-1 |
| 15.2.2.1 | Identification of Causes and Accident Description..... | 15.2-1 |
| 15.2.2.2 | Analysis of Effects and Consequences | 15.2-3 |
| 15.2.2.3 | Conclusions | 15.2-3 |
| 15.2.3 | Turbine Trip..... | 15.2-3 |
| 15.2.3.1 | Identification of Causes and Accident Description..... | 15.2-3 |
| 15.2.3.2 | Analysis of Effects and Consequences | 15.2-4 |
| 15.2.3.3 | Conclusions | 15.2-8 |

TABLE OF CONTENTS (Cont.)

| <u>Section</u> | <u>Title</u> | <u>Page</u> |
|----------------|---|---------------|
| 15.2.4 | Inadvertent Closure of Main Steam Isolation Valves..... | 15.2-8 |
| 15.2.5 | Loss of Condenser Vacuum and Other Events Resulting in Turbine Trip..... | 15.2-8 |
| 15.2.6 | Loss of ac Power to the Plant Auxiliaries | 15.2-9 |
| 15.2.6.1 | Identification of Causes and Accident Description..... | 15.2-9 |
| 15.2.6.2 | Analysis of Effects and Consequences | 15.2-10 |
| 15.2.6.3 | Conclusions | 15.2-12 |
| 15.2.7 | Loss of Normal Feedwater Flow | 15.2-13 |
| 15.2.7.1 | Identification of Causes and Accident Description..... | 15.2-13 |
| 15.2.7.2 | Analysis of Effects and Consequences | 15.2-14 |
| 15.2.7.3 | Conclusions | 15.2-16 |
| 15.2.8 | Feedwater System Pipe Break..... | 15.2-16 |
| 15.2.8.1 | Identification of Causes and Accident Description..... | 15.2-16 |
| 15.2.8.2 | Analysis of Effects and Consequences | 15.2-18 |
| 15.2.8.3 | Conclusions | 15.2-20 |
| 15.2.9 | Combined License Information..... | 15.2-21 |
| 15.2.10 | References..... | 15.2-21 |
| 15.3 | Decrease in Reactor Coolant System Flow Rate | 15.3-1 |
| 15.3.1 | Partial Loss of Forced Reactor Coolant Flow | 15.3-1 |
| 15.3.1.1 | Identification of Causes and Accident Description..... | 15.3-1 |
| 15.3.1.2 | Analysis of Effects and Consequences | 15.3-2 |
| 15.3.1.3 | Conclusions | 15.3-3 |
| 15.3.2 | Complete Loss of Forced Reactor Coolant Flow | 15.3-3 |
| 15.3.2.1 | Identification of Causes and Accident Description..... | 15.3-3 |
| 15.3.2.2 | Analysis of Effects and Consequences | 15.3-4 |
| 15.3.2.3 | Conclusions | 15.3-5 |
| 15.3.3 | Reactor Coolant Pump Shaft Seizure (Locked Rotor)..... | 15.3-5 |
| 15.3.3.1 | Identification of Causes and Accident Description..... | 15.3-5 |
| 15.3.3.2 | Analysis of Effects and Consequences | 15.3-5 |
| 15.3.3.3 | Radiological Consequences..... | 15.3-8 |
| 15.3.4 | Reactor Coolant Pump Shaft Break | 15.3-10 |
| 15.3.4.1 | Identification of Causes and Accident Description..... | 15.3-10 |
| 15.3.4.2 | Conclusion..... | 15.3-10 |
| 15.3.5 | Combined License Information..... | 15.3-11 |
| 15.3.6 | References..... | 15.3-11 |
| 15.4 | Reactivity and Power Distribution Anomalies | 15.4-1 |
| 15.4.1 | Uncontrolled Rod Cluster Control Assembly Bank Withdrawal from a Subcritical or Low-power Startup Condition..... | 15.4-1 |
| 15.4.1.1 | Identification of Causes and Accident Description..... | 15.4-1 |
| 15.4.1.2 | Analysis of Effects and Consequences | 15.4-3 |
| 15.4.1.3 | Conclusions | 15.4-5 |

TABLE OF CONTENTS (Cont.)

| <u>Section</u> | <u>Title</u> | <u>Page</u> |
|----------------|--|---------------|
| 15.4.2 | Uncontrolled Rod Cluster Control Assembly Bank Withdrawal at Power | 15.4-5 |
| 15.4.2.1 | Identification of Causes and Accident Description..... | 15.4-5 |
| 15.4.2.2 | Analysis of Effects and Consequences | 15.4-7 |
| 15.4.2.3 | Conclusions | 15.4-11 |
| 15.4.3 | Rod Cluster Control Assembly Misalignment (System Malfunction or Operator Error) | 15.4-11 |
| 15.4.3.1 | Identification of Causes and Accident Description..... | 15.4-11 |
| 15.4.3.2 | Analysis of Effects and Consequences | 15.4-14 |
| 15.4.3.3 | Conclusions | 15.4-17 |
| 15.4.4 | Startup of an Inactive Reactor Coolant Pump at an Incorrect Temperature | 15.4-17 |
| 15.4.5 | A Malfunction or Failure of the Flow Controller in a Boiling Water Reactor Loop that Results in an Increased Reactor Coolant Flow Rate | 15.4-17 |
| 15.4.6 | Chemical and Volume Control System Malfunction that Results in a Decrease in the Boron Concentration in the Reactor Coolant | 15.4-17 |
| 15.4.6.1 | Identification of Causes and Accident Description..... | 15.4-17 |
| 15.4.6.2 | Analysis of Effects and Consequences | 15.4-19 |
| 15.4.6.3 | Conclusions | 15.4-24 |
| 15.4.7 | Inadvertent Loading and Operation of a Fuel Assembly in an Improper Position | 15.4-25 |
| 15.4.7.1 | Identification of Causes and Accident Description..... | 15.4-25 |
| 15.4.7.2 | Analysis of Effects and Consequences | 15.4-25 |
| 15.4.7.3 | Conclusions | 15.4-26 |
| 15.4.8 | Spectrum of Rod Cluster Control Assembly Ejection Accidents | 15.4-27 |
| 15.4.8.1 | Identification of Causes and Accident Description..... | 15.4-27 |
| 15.4.8.2 | Analysis of Effects and Consequences | 15.4-30 |
| 15.4.8.3 | Radiological Consequences | 15.4-35 |
| 15.4.9 | Combined License Information..... | 15.4-38 |
| 15.4.10 | References..... | 15.4-38 |
| 15.5 | Increase in Reactor Coolant Inventory | 15.5-1 |
| 15.5.1 | Inadvertent Operation of the Core Makeup Tanks During Power Operation | 15.5-1 |
| 15.5.1.1 | Identification of the Causes and Accident Description..... | 15.5-1 |
| 15.5.1.2 | Analysis of Effects and Consequences | 15.5-2 |
| 15.5.1.3 | Results | 15.5-4 |
| 15.5.1.4 | Conclusions | 15.5-5 |
| 15.5.2 | Chemical and Volume Control System Malfunction That Increases Reactor Coolant Inventory | 15.5-5 |
| 15.5.2.1 | Identification of Causes and Accident Description..... | 15.5-5 |
| 15.5.2.2 | Analysis of Effects and Consequences | 15.5-7 |

TABLE OF CONTENTS (Cont.)

| <u>Section</u> | <u>Title</u> | <u>Page</u> |
|----------------|--|---------------|
| | 15.5.2.3 Results | 15.5-8 |
| | 15.5.2.4 Conclusions | 15.5-9 |
| 15.5.3 | Boiling Water Reactor Transients | 15.5-10 |
| 15.5.4 | Combined License Information..... | 15.5-10 |
| 15.5.5 | References..... | 15.5-10 |
| 15.6 | Decrease in Reactor Coolant Inventory | 15.6-1 |
| 15.6.1 | Inadvertent Opening of a Pressurizer Safety Valve or Inadvertent Operation of the ADS | 15.6-1 |
| | 15.6.1.1 Identification of Causes and Accident Description..... | 15.6-1 |
| | 15.6.1.2 Analysis of Effects and Consequences | 15.6-2 |
| | 15.6.1.3 Conclusion..... | 15.6-4 |
| 15.6.2 | Failure of Small Lines Carrying Primary Coolant Outside Containment..... | 15.6-4 |
| | 15.6.2.1 Source Term | 15.6-5 |
| | 15.6.2.2 Release Pathway | 15.6-5 |
| | 15.6.2.3 Dose Calculation Models | 15.6-5 |
| | 15.6.2.4 Analytical Assumptions and Parameters | 15.6-5 |
| | 15.6.2.5 Identification of Conservatisms | 15.6-5 |
| | 15.6.2.6 Doses | 15.6-5 |
| 15.6.3 | Steam Generator Tube Rupture..... | 15.6-6 |
| | 15.6.3.1 Identification of Cause and Accident Description | 15.6-6 |
| | 15.6.3.2 Analysis of Effects and Consequences | 15.6-9 |
| | 15.6.3.3 Radiological Consequences..... | 15.6-13 |
| | 15.6.3.4 Conclusions | 15.6-15 |
| 15.6.4 | Spectrum of Boiling Water Reactor Steam System Piping Failures Outside of Containment | 15.6-16 |
| 15.6.5 | Loss-of-coolant Accidents Resulting from a Spectrum of Postulated Piping Breaks Within the Reactor Coolant Pressure Boundary | 15.6-16 |
| | 15.6.5.1 Identification of Causes and Frequency Classification | 15.6-16 |
| | 15.6.5.2 Basis and Methodology for LOCA Analyses | 15.6-17 |
| | 15.6.5.3 Radiological Consequences..... | 15.6-19 |
| | 15.6.5.4 Core and System Performance..... | 15.6-24 |
| | 15.6.5.4A Large-break LOCA Analysis Methodology and Results | 15.6-24 |
| | 15.6.5.4B Small-break LOCA Analyses | 15.6-32 |
| | 15.6.5.4C Post-LOCA Long-Term Cooling | 15.6-48 |
| 15.6.6 | References..... | 15.6-55 |
| 15.7 | Radioactive Release from a Subsystem or Component | 15.7-1 |
| 15.7.1 | Gas Waste Management System Leak or Failure | 15.7-1 |
| 15.7.2 | Liquid Waste Management System Leak or Failure (Atmospheric Release)..... | 15.7-1 |

TABLE OF CONTENTS (Cont.)

| <u>Section</u> | <u>Title</u> | <u>Page</u> |
|--|--|---------------|
| 15.7.3 | Release of Radioactivity to the Environment Due to a Liquid Tank Failure | 15.7-1 |
| 15.7.4 | Fuel Handling Accident | 15.7-1 |
| 15.7.4.1 | Source Term | 15.7-2 |
| 15.7.4.2 | Release Pathways | 15.7-3 |
| 15.7.4.3 | Dose Calculation Models | 15.7-3 |
| 15.7.4.4 | Identification of Conservatisms | 15.7-3 |
| 15.7.4.5 | Offsite Doses | 15.7-5 |
| 15.7.5 | Spent Fuel Cask Drop Accident..... | 15.7-5 |
| 15.7.6 | Combined License Information..... | 15.7-5 |
| 15.7.7 | References..... | 15.7-5 |
| 15.8 | Anticipated Transients Without Scram..... | 15.8-1 |
| 15.8.1 | General Background | 15.8-1 |
| 15.8.2 | Anticipated Transients Without Scram in the AP1000 | 15.8-1 |
| 15.8.3 | Conclusion | 15.8-1 |
| 15.8.4 | Combined License Information..... | 15.8-1 |
| 15.8.5 | References..... | 15.8-1 |
| APPENDIX 15A EVALUATION MODELS AND PARAMETERS FOR ANALYSIS OF RADIOPHYSICAL CONSEQUENCES OF ACCIDENTS | | 15A-1 |
| 15A.1 | Offsite Dose Calculation Models | 15A-1 |
| 15A.1.1 | Immersion Dose (Effective Dose Equivalent)..... | 15A-1 |
| 15A.1.2 | Inhalation Dose (Committed Effective Dose Equivalent) | 15A-1 |
| 15A.1.3 | Total Dose (Total Effective Dose Equivalent) | 15A-2 |
| 15A.2 | Main Control Room Dose Models..... | 15A-2 |
| 15A.2.1 | Immersion Dose Models | 15A-2 |
| 15A.2.2 | Inhalation Dose | 15A-3 |
| 15A.2.3 | Total Dose (Total Effective Dose Equivalent) | 15A-3 |
| 15A.3 | General Analysis Parameters..... | 15A-3 |
| 15A.3.1 | Source Terms | 15A-3 |
| 15A.3.1.1 | Primary Coolant Source Term | 15A-3 |
| 15A.3.1.2 | Secondary Coolant Source Term | 15A-4 |
| 15A.3.1.3 | Core Source Term | 15A-4 |
| 15A.3.2 | Nuclide Parameters | 15A-4 |
| 15A.3.3 | Atmospheric Dispersion Factors | 15A-5 |
| 15A.4 | References..... | 15A-5 |
| APPENDIX 15B REMOVAL OF AIRBORNE ACTIVITY FROM THE CONTAINMENT ATMOSPHERE FOLLOWING A LOCA | | 15B-1 |
| 15B.1 | Elemental Iodine Removal | 15B-1 |
| 15B.2 | Aerosol Removal | 15B-1 |

TABLE OF CONTENTS (Cont.)

| <u>Section</u> | <u>Title</u> | <u>Page</u> |
|----------------|--|-------------|
| 15B.2.1 | Mathematical Models..... | 15B-2 |
| 15B.2.1.1 | Sedimentation..... | 15B-2 |
| 15B.2.1.2 | Diffusiophoresis | 15B-4 |
| 15B.2.1.3 | Thermophoresis | 15B-5 |
| 15B.2.2 | Other Removal Mechanisms | 15B-6 |
| 15B.2.3 | Validation of Removal Mechanisms | 15B-6 |
| 15B.2.4 | Parameters and Assumptions for Calculating Aerosol Removal Coefficients..... | 15B-6 |
| 15B.2.4.1 | Containment Geometry..... | 15B-6 |
| 15B.2.4.2 | Source Size Distribution..... | 15B-6 |
| 15B.2.4.3 | Aerosol Void Fraction | 15B-7 |
| 15B.2.4.4 | Fission Product Release Fractions | 15B-7 |
| 15B.2.4.5 | Inert Aerosol Species..... | 15B-7 |
| 15B.2.4.6 | Aerosol Release Timing and Rates..... | 15B-7 |
| 15B.2.4.7 | Containment Thermal-hydraulic Data | 15B-8 |
| 15B.2.5 | Aerosol Removal Coefficients | 15B-8 |
| 15B.3 | References | 15B-8 |

LIST OF TABLES

| <u>Table No.</u> | <u>Title</u> | <u>Page</u> |
|------------------|---|-------------|
| 15.0-1 | Nuclear Steam Supply System Power Ratings | 15.0-16 |
| 15.0-2 | Summary of Initial Conditions and Computer Codes Used (Sheets 1 – 5)..... | 15.0-17 |
| 15.0-3 | Nominal Values of Pertinent Plant Parameters Used in Accident Analyses..... | 15.0-22 |
| 15.0-4a | Protection and Safety Monitoring System Setpoints and Time Delay Assumed in Accident Analyses (Sheets 1 – 2) | 15.0-23 |
| 15.0-4b | Limiting Delay Times for Equipment Assumed in Accident Analyses | 15.0-25 |
| 15.0-5 | Determination of Maximum Power Range Neutron Flux Channel Trip Setpoint, Based on Nominal Setpoint and Inherent Typical Instrumentation Uncertainties | 15.0-26 |
| 15.0-6 | Plant Systems And Equipment Available for Transient and Accident Conditions (Sheets 1 – 4) | 15.0-27 |
| 15.0-7 | Single Failures Assumed in Accident Analyses (Sheets 1 –2) | 15.0-31 |
| 15.0-8 | Nonsafety-Related System and Equipment Used for Mitigation of Accidents | 15.0-33 |
| 15.1.2-1 | Time Sequence of Events for Incidents that Result in an Increase in Heat Removal From the Primary System (Sheets 1 – 2)..... | 15.1-25 |
| 15.1.5-1 | Parameters Used in Evaluating the Radiological Consequences of a Main Steam Line Break..... | 15.1-27 |
| 15.2-1 | Time Sequence of Events for Incidents Which Result in a Decrease in Heat Removal by the Secondary System (Sheets 1 – 7) | 15.2-22 |
| 15.3-1 | Time Sequence of Events for Incidents that Result in a Decrease in Reactor Coolant System Flow Rate | 15.3-12 |
| 15.3-2 | Summary of Results for Locked Rotor Transients (Four Reactor Coolant Pumps Operating Initially) | 15.3-13 |
| 15.3-3 | Parameters Used in Evaluating the Radiological Consequences of a Locked Rotor Accident (Sheets 1 – 2)..... | 15.3-14 |
| 15.4-1 | Time Sequence of Events for Incidents Which Result in Reactivity and Power Distribution Anomalies (Sheets 1 – 3) | 15.4-40 |
| 15.4-2 | Parameters | 15.4-43 |
| 15.4-3 | Parameters Used in the Analysis of the Rod Cluster Control Assembly Ejection Accident | 15.4-44 |
| 15.4-4 | Parameters Used in Evaluating the Radiological Consequences of a Rod Ejection Accident (Sheets 1 – 2) | 15.4-45 |
| 15.5-1 | Time Sequence of Events for Incidents Which Result in an Increase in Reactor Coolant Inventory (Sheets 1 – 2)..... | 15.5-11 |
| 15.6.1-1 | Time Sequence of Events for Incidents that Cause a Decrease in Reactor Coolant Inventory..... | 15.6-58 |
| 15.6.2-1 | Parameters Used in Evaluating the Radiological Consequences of a Small Line Break Outside Containment | 15.6-59 |
| 15.6.3-1 | Steam Generator Tube Rupture Sequence of Events..... | 15.6-60 |
| 15.6.3-2 | Steam Generator Tube Rupture Mass Release Results..... | 15.6-61 |
| 15.6.3-3 | Parameters Used in Evaluating the Radiological Consequences of a Steam Generator Tube Rupture | 15.6-62 |

LIST OF TABLES (Cont.)

| <u>Table No.</u> | <u>Title</u> | <u>Page</u> |
|------------------|---|-------------|
| 15.6.5-1 | Core Activity Releases to the Containment Atmosphere..... | 15.6-63 |
| 15.6.5-2 | Assumptions and Parameters Used in Calculating Radiological Consequences of a Loss-Of-Coolant Accident (Sheets 1 – 3) | 15.6-64 |
| 15.6.5-3 | Radiological Consequences of a Loss-of-Coolant Accident with Core Melt..... | 15.6-67 |
| 15.6.5-4 | Major Plant Parameter Assumptions Used in the Best-Estimate Large-Break LOCA Analysis | 15.6-68 |
| 15.6.5-5 | AP1000 LOCA Chronology..... | 15.6-69 |
| 15.6.5-6 | Reference Transient DECLG Break Sequence of Events..... | 15.6-70 |
| 15.6.5-7 | DECL Split Break Results..... | 15.6-71 |
| 15.6.5-8 | Best-Estimate Large-Break LOCA Results | 15.6-72 |
| 15.6.5-9 | Initial Conditions for AP1000 Small-Break LOCA Analysis..... | 15.6-73 |
| 15.6.5-10 | AP1000 ADS Parameters | 15.6-74 |
| 15.6.5-11 | Inadvertent ADS Depressurization Sequence of Events..... | 15.6-75 |
| 15.6.5-12 | 2-Inch Cold Leg Break in CLBL Line Sequence of Events | 15.6-76 |
| 15.6.5-13 | Double-Ended Injection Line Break Sequence of Events – 20 psi | 15.6-77 |
| 15.6.5-13A | Double-Ended Injection Line Break Sequence of Events – 14.7 psi | 15.6-78 |
| 15.6.5-14 | 10-Inch Cold Leg Break in Sequence of Events..... | 15.6-79 |
| 15.6.5-15 | Double-Ended Injection Line Break Sequence of Events (Entrainment Sensitivity) | 15.6-80 |
| 15.7-1 | Assumptions Used to Determine Fuel Handling Accident Radiological Consequences..... | 15.7-6 |
| 15A-1 | Reactor Coolant Iodine Concentrations for Maximum Iodine Spike of 60 µCi/g Dose Equivalent I-131..... | 15A-7 |
| 15A-2 | Iodine Appearance Rates in the Reactor Coolant | 15A-7 |
| 15A-3 | Reactor Core Source Term (Sheets 1 – 2) | 15A-8 |
| 15A-4 | Nuclide Parameters (Sheets 1 – 4)..... | 15A-10 |
| 15A-5 | Offsite Atmospheric Dispersion Factors (χ/Q) for Accident Dose Analysis..... | 15A-14 |
| 15A-6 | Control Room Atmospheric Dispersion Factors (χ/Q) for Accident Dose Analysis..... | 15A-15 |
| 15A-7 | Control Room Source/Receptor Data for Determination of Atmospheric Dispersion Factors | 15A-17 |
| 15B-1 | Aerosol Removal Coefficients in the AP1000 Containment Following a Design Basis LOCA With Core Melt (Sheets 1 – 3) | 15B-10 |

LIST OF FIGURES

| <u>Figure No.</u> | <u>Title</u> | <u>Page</u> |
|-------------------|---|-------------|
| 15.0.3-1 | Overpower and Overtemperature ΔT Protection | 15.0-34 |
| 15.0.3-2 | AP1000 Loop Layout..... | 15.0-35 |
| 15.0.4-1 | Doppler Power Coefficient used in Accident Analysis | 15.0-36 |
| 15.0.5-1 | RCCA Position Versus Time to Dashpot | 15.0-37 |
| 15.0.5-2 | Normalized Rod Worth Versus Position | 15.0-38 |
| 15.0.5-3 | Normalized RCCA Bank Reactivity Worth Versus Drop Time | 15.0-39 |
| 15.1.2-1 | Feedwater Control Valve Malfunction Nuclear Power..... | 15.1-28 |
| 15.1.2-2 | Feedwater Control Valve Malfunction Loop ΔT | 15.1-29 |
| 15.1.2-3 | Feedwater Control Valve Malfunction Core Coolant Mass Flow..... | 15.1-30 |
| 15.1.3-1 | Nuclear Power (Fraction of Nominal) Versus Time for 10-percent Step Load Increase, Manual Control and Minimum Moderator Feedback..... | 15.1-31 |
| 15.1.3-2 | Pressurizer Pressure (psia) Versus Time for 10-percent Step Load Increase, Manual Control and Minimum Moderator Feedback..... | 15.1-32 |
| 15.1.3-3 | Pressurizer Water Volume (ft^3) Versus Time for 10-percent Step Load Increase, Manual Control and Minimum Moderator Feedback | 15.1-33 |
| 15.1.3-4 | Core Average Temperature ($^{\circ}\text{F}$) Versus Time for 10-percent Step Load Increase, Manual Control and Minimum Moderator Feedback | 15.1-34 |
| 15.1.3-5 | DNBR Versus Time for 10-percent Step Load Increase, Manual Control and Minimum Moderator Feedback | 15.1-35 |
| 15.1.3-6 | Nuclear Power (Fraction of Nominal) Versus Time for 10-percent Step Load Increase, Manual Control and Maximum Moderator Feedback | 15.1-36 |
| 15.1.3-7 | Pressurizer Pressure (psia) Versus Time for 10-percent Step Load Increase, Manual Control and Maximum Moderator Feedback | 15.1-37 |
| 15.1.3-8 | Pressurizer Water Volume (ft^3) Versus Time for 10-percent Step Load Increase, Manual Control and Maximum Moderator Feedback | 15.1-38 |
| 15.1.3-9 | Core Average Temperature ($^{\circ}\text{F}$) Versus Time for 10-percent Step Load Increase, Manual Control and Maximum Moderator Feedback | 15.1-39 |
| 15.1.3-10 | DNBR Versus Time for 10-percent Step Load Increase, Manual Control and Maximum Moderator Feedback..... | 15.1-40 |
| 15.1.3-11 | Nuclear Power (Fraction of Nominal) Versus Time for 10-percent Step Load Increase, Automatic Control and Minimum Moderator Feedback | 15.1-41 |
| 15.1.3-12 | Pressurizer Pressure (psia) Versus Time for 10-percent Step Load Increase, Automatic Control and Minimum Moderator Feedback | 15.1-42 |
| 15.1.3-13 | Pressurizer Water Volume (ft^3) Versus Time for 10-percent Step Load Increase, Automatic Control and Minimum Moderator Feedback | 15.1-43 |
| 15.1.3-14 | Core Average Temperature ($^{\circ}\text{F}$) Versus Time for 10-percent Step Load Increase, Automatic Control and Minimum Moderator Feedback | 15.1-44 |
| 15.1.3-15 | DNBR Versus Time for 10-percent Step Load Increase, Automatic Control and Minimum Moderator Feedback | 15.1-45 |
| 15.1.3-16 | Nuclear Power (Fraction of Nominal) Versus Time for 10-percent Step Load Increase, Automatic Control and Maximum Moderator Feedback..... | 15.1-46 |

LIST OF FIGURES (Cont.)

| <u>Figure No.</u> | <u>Title</u> | <u>Page</u> |
|-------------------|--|-------------|
| 15.1.3-17 | Pressurizer Pressure (psia) Versus Time for 10-percent Step Load Increase, Automatic Control and Maximum Moderator Feedback..... | 15.1-47 |
| 15.1.3-18 | Pressurizer Water Volume (ft ³) Versus Time for 10-percent Step Load Increase, Automatic Control and Maximum Moderator Feedback..... | 15.1-48 |
| 15.1.3-19 | Core Average Temperature (°F) Versus Time for 10-percent Step Load Increase, Automatic Control and Maximum Moderator Feedback..... | 15.1-49 |
| 15.1.3-20 | DNBR Versus Time for 10-percent Step Load Increase, Automatic Control and Maximum Moderator Feedback | 15.1-50 |
| 15.1.4-1 | K _{eff} Versus Core Inlet Temperature Steam Line Break Events..... | 15.1-51 |
| 15.1.4-2 | Nuclear Power Transient Inadvertent Opening of a Steam Generator Relief or Safety Valve | 15.1-52 |
| 15.1.4-3 | Core Heat Flux Transient Inadvertent Opening of a Steam Generator Relief or Safety Valve | 15.1-53 |
| 15.1.4-4 | Loop 1 Reactor Coolant Temperatures Inadvertent Opening of a Steam Generator Relief or Safety Valve..... | 15.1-54 |
| 15.1.4-5 | Loop 2 (Faulted Loop) Reactor Coolant Temperatures Inadvertent Opening of a Steam Generator Relief or Safety Valve..... | 15.1-55 |
| 15.1.4-6 | Reactor Coolant System Pressure Transient Inadvertent Opening of a Steam Generator Relief or Safety Valve..... | 15.1-56 |
| 15.1.4-7 | Pressurizer Water Volume Transient Inadvertent Opening of a Steam Generator Relief or Safety Valve..... | 15.1-57 |
| 15.1.4-8 | Core Flow Transient Inadvertent Opening of a Steam Generator Relief or Safety Valve..... | 15.1-58 |
| 15.1.4-9 | Feedwater Flow Transient Inadvertent Opening of a Steam Generator Relief or Safety Valve | 15.1-59 |
| 15.1.4-10 | Core Boron Transient Inadvertent Opening of a Steam Generator Relief or Safety Valve | 15.1-60 |
| 15.1.4-11 | Steam Pressure Transient Inadvertent Opening of a Steam Generator Relief or Safety Valve | 15.1-61 |
| 15.1.4-12 | Steam Flow Transient Inadvertent Opening of a Steam Generator Relief or Safety Valve | 15.1-62 |
| 15.1.5-1 | Nuclear Power Transient Steam System Piping Feature..... | 15.1-63 |
| 15.1.5-2 | Core Heat Flux Transient Steam System Piping Failure | 15.1-64 |
| 15.1.5-3 | Loop 1 Reactor Coolant Temperatures Steam System Piping Failure | 15.1-65 |
| 15.1.5-4 | Loop 2 Reactor Coolant Temperatures Steam System Piping Failure | 15.1-66 |
| 15.1.5-5 | Reactor Coolant System Pressure Transient Steam System Piping Failure | 15.1-67 |
| 15.1.5-6 | Pressurizer Water Volume Transient Steam System Piping Failure | 15.1-68 |
| 15.1.5-7 | Core Flow Transient Steam System Piping Failure | 15.1-69 |
| 15.1.5-8 | Feedwater Flow Transient Steam System Piping Failure | 15.1-70 |
| 15.1.5-9 | Core Boron Transient Steam System Piping Failure | 15.1-71 |
| 15.1.5-10 | Steam Pressure Transient Steam System Piping Failure..... | 15.1-72 |
| 15.1.5-11 | Steam Flow Transient Steam System Piping Failure..... | 15.1-73 |

LIST OF FIGURES (Cont.)

| <u>Figure No.</u> | <u>Title</u> | <u>Page</u> |
|-------------------|--|-------------|
| 15.1.5-12 | Core Makeup Tank Injection Flow Steam System Piping Failure..... | 15.1-74 |
| 15.1.5-13 | Core Makeup Tank Water Volume Steam System Piping Failure..... | 15.1-75 |
| 15.1.6-1 | Nuclear Power Transient Inadvertent Operation of the PRHR | 15.1-76 |
| 15.1.6-2 | Core Heat Flux Transient Inadvertent Operation of the PRHR | 15.1-77 |
| 15.1.6-3 | Reactor Vessel Inlet Temperature Transient Inadvertent Operation of the PRHR | 15.1-78 |
| 15.1.6-4 | Reactor Coolant System Pressure Transient Inadvertent Operation of the PRHR | 15.1-79 |
| 15.1.6-5 | Reactor Coolant System Flow Transient Inadvertent Operation of the PRHR | 15.1-80 |
| 15.1.6-6 | DNBR Transient Inadvertent Operation of the PRHR | 15.1-81 |
| 15.1.6-7 | PRHR Flow Transient Inadvertent Operation of the PRHR | 15.1-82 |
| 15.1.6-8 | PRHR Heat Transfer Transient Inadvertent Operation of the PRHR | 15.1-83 |
| 15.2.3-1 | Nuclear Power (Fraction of Nominal) versus Time for Turbine Trip Accident with Pressurizer Spray and Minimum Moderator Feedback | 15.2-29 |
| 15.2.3-2 | Pressurizer Pressure (psia) versus Time for Turbine Trip Accident with Pressurizer Spray and Minimum Moderator Feedback..... | 15.2-30 |
| 15.2.3-3 | Pressurizer Water Volume (ft^3) versus Time for Turbine Trip Accident with Pressurizer Spray and Minimum Moderator Feedback..... | 15.2-31 |
| 15.2.3-4 | Vessel Inlet Temperature ($^{\circ}\text{F}$) versus Time for Turbine Trip Accident with Pressurizer Spray and Minimum Moderator Feedback..... | 15.2-32 |
| 15.2.3-5 | Vessel Average Temperature ($^{\circ}\text{F}$) versus Time for Turbine Trip Accident with Pressurizer Spray and Minimum Moderator Feedback..... | 15.2-33 |
| 15.2.3-6 | DNBR versus Time for Turbine Trip Accident with Pressurizer Spray and Minimum Moderator Feedback | 15.2-34 |
| 15.2.3-7 | Core Mass Flow Rate (Fraction of Initial) versus Time for Turbine Trip Accident with Pressurizer Spray and Minimum Moderator Feedback | 15.2-35 |
| 15.2.3-8 | Nuclear Power (Fraction of Nominal) versus Time for Turbine Trip Accident with Pressurizer Spray and Maximum Moderator Feedback..... | 15.2-36 |
| 15.2.3-9 | Pressurizer Pressure (psia) versus Time for Turbine Trip Accident with Pressurizer Spray and Maximum Moderator Feedback | 15.2-37 |
| 15.2.3-10 | Pressurizer Water Volume (ft^3) versus Time for Turbine Trip Accident with Pressurizer Spray and Maximum Moderator Feedback | 15.2-38 |
| 15.2.3-11 | Vessel Inlet Temperature ($^{\circ}\text{F}$) versus Time for Turbine Trip Accident with Pressurizer Spray and Maximum Moderator Feedback | 15.2-39 |
| 15.2.3-12 | Vessel Average Temperature ($^{\circ}\text{F}$) versus Time for Turbine Trip Accident with Pressurizer Spray and Maximum Moderator Feedback | 15.2-40 |
| 15.2.3-13 | DNBR versus Time for Turbine Trip Accident with Pressurizer Spray and Maximum Moderator Feedback..... | 15.2-41 |
| 15.2.3-14 | Core Mass Flow Rate (Fraction of Initial) versus Time for Turbine Trip Accident with Pressurizer Spray and Maximum Moderator Feedback..... | 15.2-42 |

LIST OF FIGURES (Cont.)

| <u>Figure No.</u> | <u>Title</u> | <u>Page</u> |
|-------------------|---|-------------|
| 15.2.3-15 | Nuclear Power (Fraction of Nominal) versus Time for Turbine Trip Accident Without Pressurizer Spray and Minimum Moderator Feedback | 15.2-43 |
| 15.2.3-16 | Pressurizer Pressure (psia) versus Time for Turbine Trip Accident Without Pressurizer Spray and Minimum Moderator Feedback..... | 15.2-44 |
| 15.2.3-17 | Pressurizer Water Volume (ft^3) versus Time for Turbine Trip Accident Without Pressurizer Spray and Minimum Moderator Feedback..... | 15.2-45 |
| 15.2.3-18 | Vessel Inlet Temperature ($^{\circ}\text{F}$) versus Time for Turbine Trip Accident Without Pressurizer Spray and Minimum Moderator Feedback..... | 15.2-46 |
| 15.2.3-19 | Vessel Average Temperature ($^{\circ}\text{F}$) versus Time for Turbine Trip Accident Without Pressurizer Spray and Minimum Moderator Feedback..... | 15.2-47 |
| 15.2.3-20 | Core Mass Flow Rate (Fraction of Initial) versus Time for Turbine Trip Accident Without Pressurizer Spray and Minimum Moderator Feedback | 15.2-48 |
| 15.2.3-21 | Nuclear Power (Fraction of Nominal) versus Time for Turbine Trip Accident Without Pressurizer Spray and Maximum Moderator Feedback..... | 15.2-49 |
| 15.2.3-22 | Pressurizer Pressure (psia) versus Time for Turbine Trip Accident Without Pressurizer Spray and Maximum Moderator Feedback..... | 15.2-50 |
| 15.2.3-23 | Pressurizer Water Volume (ft^3) versus Time for Turbine Trip Accident Without Pressurizer Spray and Maximum Moderator Feedback..... | 15.2-51 |
| 15.2.3-24 | Vessel Inlet Temperature ($^{\circ}\text{F}$) versus Time for Turbine Trip Accident Without Pressurizer Spray and Maximum Moderator Feedback | 15.2-52 |
| 15.2.3-25 | Vessel Average Temperature ($^{\circ}\text{F}$) versus Time for Turbine Trip Accident Without Pressurizer Spray and Maximum Moderator Feedback..... | 15.2-53 |
| 15.2.3-26 | Core Mass Flow Rate (Fraction of Initial) versus Time for Turbine Trip Accident Without Pressurizer Spray and Maximum Moderator Feedback..... | 15.2-54 |
| 15.2.6-1 | Nuclear Power Transient for Loss of ac Power to the Plant Auxiliaries..... | 15.2-55 |
| 15.2.6-2 | Core Heat Flux Transient for Loss of ac Power to the Plant Auxiliaries | 15.2-56 |
| 15.2.6-3 | Pressurizer Pressure Transient for Loss of ac Power to the Plant Auxiliaries | 15.2-57 |
| 15.2.6-4 | Pressurizer Water Volume Transient for Loss of ac Power to the Plant Auxiliaries..... | 15.2-58 |
| 15.2.6-5 | Reactor Coolant System Temperature Transients in Loop Containing the PRHR for Loss of ac Power to the Plant Auxiliaries | 15.2-59 |
| 15.2.6-6 | Reactor Coolant System Temperature Transients in Loop Not Containing the PRHR for Loss of ac Power to the Plant Auxiliaries | 15.2-60 |
| 15.2.6-7 | Steam Generator Pressure Transient for Loss of ac Power to the Plant Auxiliaries..... | 15.2-61 |
| 15.2.6-8 | PRHR Flow Rate Transient for Loss of ac Power to the Plant Auxiliaries..... | 15.2-62 |
| 15.2.6-9 | PRHR Heat Flux Transient for Loss of ac Power to the Plant Auxiliaries | 15.2-63 |
| 15.2.6-10 | Reactor Coolant Volumetric Flow Rate Transient for Loss of ac Power to the Plant Auxiliaries | 15.2-64 |
| 15.2.6-11 | Steam Generator Inventory Transient for Loss of ac Power to the Plant Auxiliaries..... | 15.2-65 |
| 15.2.6-12 | DNB Ratio Transient for Loss of ac Power to the Plant Auxiliaries | 15.2-66 |

LIST OF FIGURES (Cont.)

| <u>Figure No.</u> | <u>Title</u> | <u>Page</u> |
|-------------------|---|-------------|
| 15.2.7-1 | Nuclear Power Transient for Loss of Normal Feedwater Flow | 15.2-67 |
| 15.2.7-2 | Reactor Coolant System Volumetric Flow Transient for Loss of Normal Feedwater Flow..... | 15.2-68 |
| 15.2.7-3 | Reactor Coolant System Temperature Transients in Loop Containing the PRHR for Loss Normal Feedwater Flow..... | 15.2-69 |
| 15.2.7-4 | Reactor Coolant System Temperature Transients in Loop Not Containing the PRHR for Loss of Normal Feedwater Flow..... | 15.2-70 |
| 15.2.7-5 | Pressurizer Pressure Transient for Loss of Normal Feedwater Flow | 15.2-71 |
| 15.2.7-6 | Pressurizer Water Volume Transient for Loss of Normal Feedwater Flow | 15.2-72 |
| 15.2.7-7 | Steam Generator Pressure Transient for Loss of Normal Feedwater Flow..... | 15.2-73 |
| 15.2.7-8 | Steam Generator Inventory Transient for Loss of Normal Feedwater Flow | 15.2-74 |
| 15.2.7-9 | PRHR Heat Flux Transient for Loss of Normal Feedwater Flow..... | 15.2-75 |
| 15.2.7-10 | CMT Injection Flow Rate Transient for Loss of Normal Feedwater Flow..... | 15.2-76 |
| 15.2.8-1 | Nuclear Power Transient for Main Feedwater Line Rupture..... | 15.2-77 |
| 15.2.8-2 | Core Heat Flux Transient for Main Feedwater Line Rupture..... | 15.2-78 |
| 15.2.8-3 | Faulted Loop Reactor Coolant System Temperature Transients for Main Feedwater Line Rupture..... | 15.2-79 |
| 15.2.8-4 | Intact Loop Reactor Coolant System Temperature Transients for Main Feedwater Line Rupture..... | 15.2-80 |
| 15.2.8-5 | Pressurizer Pressure Transient for Main Feedwater Line Rupture | 15.2-81 |
| 15.2.8-6 | Pressurizer Water Volume Transient for Main Feedwater Line Rupture | 15.2-82 |
| 15.2.8-7 | Steam Generator Pressure Transient for Main Feedwater Line Rupture | 15.2-83 |
| 15.2.8-8 | PRHR Flow Rate Transient for Main Feedwater Line Rupture..... | 15.2-84 |
| 15.2.8-9 | PRHR Heat Flux Transient for Main Feedwater Line Rupture | 15.2-85 |
| 15.2.8-10 | CMT Injection Flow Rate Transient for Main Feedwater Line Rupture | 15.2-86 |
| 15.3.1-1 | Core Mass Flow Transient for Four Cold Legs in Operation, Two Pumps Coasting Down..... | 15.3-16 |
| 15.3.1-2 | Nuclear Power Transient for Four Cold Legs in Operation, Two Pumps Coasting Down..... | 15.3-17 |
| 15.3.1-3 | Pressurizer Pressure Transient for Four Cold Legs in Operation, Two Pumps Coasting Down..... | 15.3-18 |
| 15.3.1-4 | Average Channel Heat Flux Transient for Four Cold Legs in Operation, Two Pumps Coasting Down | 15.3-19 |
| 15.3.1-5 | Hot Channel Heat Flux Transient for Four Cold Legs in Operation, Two Pumps Coasting Down | 15.3-20 |
| 15.3.1-6 | DNB Transient for Four Cold Legs in Operation, Two Pumps Coasting Down..... | 15.3-21 |
| 15.3.2-1 | Flow Transient for Four Cold Legs in Operation, Four Pumps Coasting Down..... | 15.3-22 |
| 15.3.2-2 | Nuclear Power Transient for Four Cold Legs in Operation, Four Pumps Coasting Down..... | 15.3-23 |
| 15.3.2-3 | Pressurizer Pressure Transient for Four Cold Legs in Operation, Four Pumps Coasting Down..... | 15.3-24 |

LIST OF FIGURES (Cont.)

| <u>Figure No.</u> | <u>Title</u> | <u>Page</u> |
|-------------------|---|-------------|
| 15.3.2-4 | Average Channel Heat Flux Transient for Four Cold Legs in Operation, Four Pumps Coasting Down..... | 15.3-25 |
| 15.3.2-5 | Hot Channel Heat Flux Transient for Four Cold Legs in Operation, Four Pumps Coasting Down..... | 15.3-26 |
| 15.3.2-6 | DNBR Transient for Four Cold Legs in Operation, Four Pumps Coasting Down..... | 15.3-27 |
| 15.3.3-1 | Core Mass Flow Transient for Four Cold Legs in Operation, One Locked Rotor | 15.3-28 |
| 15.3.3-2 | Faulted Loop Volumetric Flow Transient for Four Cold Legs in Operation, One Locked Rotor | 15.3-29 |
| 15.3.3-3 | Peak Reactor Coolant Pressure for Four Cold Legs in Operation, One Locked Rotor | 15.3-30 |
| 15.3.3-4 | Average Channel Heat Flux Transient for Four Cold Legs in Operation, One Locked Rotor | 15.3-31 |
| 15.3.3-5 | Hot Channel Heat Flux Transient for Four Cold Legs in Operation, One Locked Rotor | 15.3-32 |
| 15.3.3-6 | Nuclear Power Transient for Four Cold Legs in Operation, One Locked Rotor | 15.3-33 |
| 15.3.3-7 | Cladding Inside Temperature Transient for Four Cold Legs in Operation, One Locked Rotor | 15.3-34 |
| 15.4.1-1 | RCCA Withdrawal from Subcritical Nuclear Power..... | 15.4-47 |
| 15.4.1-2 | RCCA Withdrawal from Subcritical Average Channel Core Heat Flux | 15.4-48 |
| 15.4.1-3 | RCCA Withdrawal from Subcritical Hot Spot Fuel Average Temperature (Sheet 1 of 2)..... | 15.4-49 |
| 15.4.1-3 | RCCA Withdrawal from Subcritical Hot Spot Cladding Inner Temperature (Sheet 2 of 2)..... | 15.4-50 |
| 15.4.2-1 | Nuclear Power Transient for an Uncontrolled RCCA Bank Withdrawal from Full Power With Maximum Reactivity Feedback (75 pcm/s)..... | 15.4-51 |
| 15.4.2-2 | Thermal Flux Transient for an Uncontrolled RCCA Bank Withdrawal from Full Power With Maximum Reactivity Feedback (75 pcm/s)..... | 15.4-52 |
| 15.4.2-3 | Pressurizer Pressure Transient for an Uncontrolled RCCA Bank Withdrawal from Full Power With Maximum Reactivity Feedback (75 pcm/s)..... | 15.4-53 |
| 15.4.2-4 | Pressurizer Water Volume Transient for an Uncontrolled RCCA Bank Withdrawal from Full Power With Maximum Reactivity Feedback (75 pcm/s) | 15.4-54 |
| 15.4.2-5 | Core Coolant Average Temperature Transient for an Uncontrolled RCCA Bank Withdrawal from Full Power With Maximum Reactivity Feedback (75 pcm/s) | 15.4-55 |
| 15.4.2-6 | DNBR Transient for an Uncontrolled RCCA Bank Withdrawal from Full Power With Maximum Reactivity Feedback (75 pcm/s) | 15.4-56 |
| 15.4.2-7 | Core Mass Flow Rate Transient for an Uncontrolled RCCA Bank Withdrawal from Full Power With Maximum Reactivity Feedback (75 pcm/s) | 15.4-57 |

LIST OF FIGURES (Cont.)

| <u>Figure No.</u> | <u>Title</u> | <u>Page</u> |
|-------------------|--|-------------|
| 15.4.2-8 | Nuclear Power Transient for an Uncontrolled RCCA Bank Withdrawal from Full Power With Maximum Reactivity Feedback (3 pcm/s)..... | 15.4-58 |
| 15.4.2-9 | Thermal Flux Transient for an Uncontrolled RCCA Bank Withdrawal from Full Power With Maximum Reactivity Feedback (3 pcm/s)..... | 15.4-59 |
| 15.4.2-10 | Pressurizer Pressure Transient for an Uncontrolled RCCA Bank Withdrawal from Full Power With Maximum Reactivity Feedback (3 pcm/s)..... | 15.4-60 |
| 15.4.2-11 | Pressurizer Water Volume Transient for an Uncontrolled RCCA Bank Withdrawal from Full Power With Maximum Reactivity Feedback (3 pcm/s) | 15.4-61 |
| 15.4.2-12 | Core Coolant Average Temperature Transient for an Uncontrolled RCCA Bank Withdrawal from Full Power With Maximum Reactivity Feedback (3 pcm/s) | 15.4-62 |
| 15.4.2-13 | DNBR Transient for an Uncontrolled RCCA Bank Withdrawal from Full Power With Maximum Reactivity Feedback (3 pcm/s) | 15.4-63 |
| 15.4.2-14 | Core Mass Flow Rate Transient for an Uncontrolled RCCA Bank Withdrawal from Full Power With Maximum Reactivity Feedback (3 pcm/s) | 15.4-64 |
| 15.4.2-15 | Minimum DNBR Versus Reactivity Insertion Rate for Rod Withdrawal at 100-percent Power..... | 15.4-65 |
| 15.4.2-16 | Minimum DNBR Versus Reactivity Insertion Rate for Rod Withdrawal at 60-percent Power..... | 15.4-66 |
| 15.4.2-17 | Minimum DNBR Versus Reactivity Insertion Rate for Rod Withdrawal at 10-percent Power..... | 15.4-67 |
| 15.4.3-1 | Nuclear Power Transient for Dropped RCCA | 15.4-68 |
| 15.4.3-2 | Core Heat Flux Transient for Dropped RCCA | 15.4-69 |
| 15.4.3-3 | Reactor Coolant System Pressure Transient for Dropped RCCA | 15.4-70 |
| 15.4.3-4 | RCS Average Temperature Transient for Dropped RCCA | 15.4-71 |
| 15.4.7-1 | Representative Percent Change in Local Assembly Average Power for Interchange Between Region 1 and Region 3 Assembly | 15.4-72 |
| 15.4.7-2 | Representative Percent Change in Local Assembly Average Power for Interchange Between Region 1 and Region 2 Assembly with the BP Rods Transferred to Region 1 Assembly | 15.4-73 |
| 15.4.7-3 | Representative Percent Change in Local Assembly Average Power for Enrichment Error (Region 2 Assembly Loaded into Core Central Position) | 15.4-74 |
| 15.4.7-4 | Representative Percent Change in Local Assembly Average Power for Loading Region 2 Assembly into Region 1 Position Near Core Periphery | 15.4-75 |
| 15.4.8-1 | Nuclear Power Transient Versus Time at Beginning of Life, Full Power | 15.4-76 |
| 15.4.8-2 | Hot Spot Fuel, Average Fuel, and Outer Cladding Temperature Versus Time at Beginning of Life, Full Power..... | 15.4-77 |
| 15.4.8-3 | Nuclear Power Transient Versus Time at End of Life, Zero Power | 15.4-78 |
| 15.4.8-4 | Hot Spot Fuel, Average Fuel, and Outer Cladding Temperature Versus Time at End of Life, Zero Power..... | 15.4-79 |
| 15.5.1-1 | Core Nuclear Power Transient for Inadvertent Operation of the Emergency Core Cooling System Due to a Spurious Opening of the Core Makeup Tank Discharge Valves..... | 15.5-13 |

LIST OF FIGURES (Cont.)

| <u>Figure No.</u> | <u>Title</u> | <u>Page</u> |
|-------------------|--|-------------|
| 15.5.1-2 | RCS Temperature Transient in Loop Containing the PRHR for Inadvertent Operation of the Emergency Core Cooling System Due to a Spurious Opening of the Core Makeup Tank Discharge Valves..... | 15.5-14 |
| 15.5.1-3 | RCS Temperature Transient in Loop Not Containing the PRHR for Inadvertent Operation of the Emergency Core Cooling System Due to a Spurious Opening of the Core Makeup Tank Discharge Valves..... | 15.5-15 |
| 15.5.1-4 | Pressurizer Pressure Transient for Inadvertent Operation of the Emergency Core Cooling System Due to a Spurious Opening of the Core Makeup Tank Discharge Valves..... | 15.5-16 |
| 15.5.1-5 | Pressurizer Water Volume Transient for Inadvertent Operation of the Emergency Core Cooling System Due to a Spurious Opening of the Core Makeup Tank Discharge Valves..... | 15.5-17 |
| 15.5.1-6 | DNBR Transient for Inadvertent Operation of the Emergency Core Cooling System Due to a Spurious Opening of the Core Makeup Tank Discharge Valves | 15.5-18 |
| 15.5.1-7 | Steam Generator Pressure Transient for Inadvertent Operation of the Emergency Core Cooling System Due to a Spurious Opening of the Core Makeup Tank Discharge Valves..... | 15.5-19 |
| 15.5.1-8 | Inadvertent Actuated CMT Flow Rate Transient for Inadvertent Operation of the Emergency Core Cooling System Due to a Spurious Opening of the Core Makeup Tank Discharge Valves | 15.5-20 |
| 15.5.1-9 | Intact CMT Flow Rate Transient for Inadvertent Operation of the Emergency Core Cooling System Due to a Spurious Opening of the Core Makeup Tank Discharge Valves | 15.5-21 |
| 15.5.1-10 | PRHR and Core Heat Flux Transient for Inadvertent Operation of the Emergency Core Cooling System Due to a Spurious Opening of the Core Makeup Tank Discharge Valves | 15.5-22 |
| 15.5.1-11 | PRHR Flow Rate Transient for Inadvertent Operation of the Emergency Core Cooling System Due to a Spurious Opening of the Core Makeup Tank Discharge Valves | 15.5-23 |
| 15.5.2-1 | Core Nuclear Power Transient for Chemical and Volume Control System Malfunction | 15.5-24 |
| 15.5.2-2 | RCS Temperature Transient in Loop Containing the PRHR for Chemical and Volume Control System Malfunction | 15.5-25 |
| 15.5.2-3 | RCS Temperature Transient in Loop Not Containing the PRHR for Chemical and Volume Control System Malfunction | 15.5-26 |
| 15.5.2-4 | Pressurizer Pressure Transient for Chemical and Volume Control System Malfunction | 15.5-27 |
| 15.5.2-5 | Pressurizer Water Volume Transient for Chemical and Volume Control System Malfunction | 15.5-28 |
| 15.5.2-6 | DNBR Transient for Chemical and Volume Control System Malfunction | 15.5-29 |
| 15.5.2-7 | CVS Flow Rate Transient for Chemical and Volume Control System Malfunction | 15.5-30 |

LIST OF FIGURES (Cont.)

| <u>Figure No.</u> | <u>Title</u> | <u>Page</u> |
|-------------------|--|-------------|
| 15.5.2-8 | Steam Generator Pressure Transient for Chemical and Volume Control System Malfunction | 15.5-31 |
| 15.5.2-9 | CMT Injection Line and Balance Line Flow Transient for Chemical and Volume Control System Malfunction..... | 15.5-32 |
| 15.5.2-10 | PRHR and Core Heat Flux Transient for Chemical and Volume Control System Malfunction | 15.5-33 |
| 15.5.2-11 | PRHR Flow Rate Transient for Chemical and Volume Control System Malfunction..... | 15.5-34 |
| 15.6.1-1 | Nuclear Power Transient Inadvertent Opening of a Pressurizer Safety Valve..... | 15.6-81 |
| 15.6.1-2 | DNBR Transient Inadvertent Opening of a Pressurizer Safety Valve | 15.6-82 |
| 15.6.1-3 | Pressurizer Pressure Transient Inadvertent Opening of a Pressurizer Safety Valve .. | 15.6-83 |
| 15.6.1-4 | Vessel Average Temperature Inadvertent Opening of a Pressurizer Safety Valve | 15.6-84 |
| 15.6.1-5 | Core Mass Flow Rate Inadvertent Opening of a Pressurizer Safety Valve..... | 15.6-85 |
| 15.6.1-6 | Nuclear Power Transient Inadvertent Opening of Two ADS Stage 1 Trains | 15.6-86 |
| 15.6.1-7 | DNBR Transient Inadvertent Opening of Two ADS Stage 1 Trains..... | 15.6-87 |
| 15.6.1-8 | Nuclear Power Transient Inadvertent Opening of Two ADS Stage 1 Trains | 15.6-88 |
| 15.6.1-9 | Nuclear Power Transient Inadvertent Opening of Two ADS Stage 1 Trains | 15.6-89 |
| 15.6.1-10 | Core Mass Flow Rate Inadvertent Opening of Two ADS Stage 1 Trains | 15.6-90 |
| 15.6.3-1 | Pressurizer Level for SGTR | 15.6-91 |
| 15.6.3-2 | Reactor Coolant System Pressure for SGTR | 15.6-92 |
| 15.6.3-3 | Secondary Pressure for SGTR..... | 15.6-93 |
| 15.6.3-4 | Intact Loop Hot and Cold Leg Reactor Coolant System Temperature for SGTR..... | 15.6-94 |
| 15.6.3-5 | Primary-to-Secondary Break Flow Rate for SGTR | 15.6-95 |
| 15.6.3-6 | Faulted Steam Generator Water Volume for SGTR | 15.6-96 |
| 15.6.3-7 | Faulted Steam Generator Mass Release Rate to the Atmosphere for SGTR | 15.6-97 |
| 15.6.3-8 | Intact Steam Generator Mass Release Rate to the Atmosphere for SGTR | 15.6-98 |
| 15.6.3-9 | Faulted Loop Chemical and Volume Control System and Core Makeup Tank Injection Flow for SGTR | 15.6-99 |
| 15.6.3-10 | Integrated Flashed Break Flow for SGTR | 15.6-100 |
| 15.6.5.4A-1 | PCT Among All Elevations for Each Fuel Rod..... | 15.6-101 |
| 15.6.5.4A-2 | Hot Rod Cladding Temperature Transient, PCT Elevation | 15.6-102 |
| 15.6.5.4A-3 | Hot Assembly Exit Vapor, Entrained Drop, Liquid Flow Rates | 15.6-103 |
| 15.6.5.4A-4 | Core Pressure | 15.6-104 |
| 15.6.5.4A-5 | Accumulator Flow Rate..... | 15.6-105 |
| 15.6.5.4A-6 | Intact Loop Core Makeup Tank Flow Rate | 15.6-106 |
| 15.6.5.4A-7 | Peripheral Assemblies Exit Vapor, Entrained Drop, Liquid Flow Rates..... | 15.6-107 |
| 15.6.5.4A-8 | Guide Tube Assemblies Exit Vapor, Entrained Drop, Liquid Flow Rates | 15.6-108 |
| 15.6.5.4A-9 | Open Hole Assemblies Exit Vapor, Entrained Drop, Liquid Flow Rates..... | 15.6-109 |
| 15.6.5.4A-10 | Steam Generator Side DECLG Break Flow Rate | 15.6-110 |
| 15.6.5.4A-11 | Vessel Side DECLG Break Flow Rate | 15.6-111 |
| 15.6.5.4A-12 | Core and Downcomer Collapsed Liquid Levels..... | 15.6-112 |
| 15.6.5.4B-1 | Inadvertent ADS – RCS Pressure..... | 15.6-113 |
| 15.6.5.4B-2 | Inadvertent ADS – Pressurizer Mixture Level | 15.6-114 |
| 15.6.5.4B-3 | Inadvertent ADS – ADS 1-3 Liquid Discharge..... | 15.6-115 |

LIST OF FIGURES (Cont.)

| <u>Figure No.</u> | <u>Title</u> | <u>Page</u> |
|-------------------|--|-------------|
| 15.6.5.4B-4 | Inadvertent ADS – ADS 1-3 Vapor Discharge..... | 15.6-116 |
| 15.6.5.4B-5 | Inadvertent ADS – CMT-1 Injection Rate | 15.6-117 |
| 15.6.5.4B-6 | Inadvertent ADS – CMT-2 Injection Rate | 15.6-118 |
| 15.6.5.4B-7 | Inadvertent ADS – CMT-1 Mixture Level | 15.6-119 |
| 15.6.5.4B-8 | Inadvertent ADS – CMT-2 Mixture Level | 15.6-120 |
| 15.6.5.4B-9 | Inadvertent ADS – Downcomer Mixture Level | 15.6-121 |
| 15.6.5.4B-10 | Inadvertent ADS – Accumulator-1 Injection Rate..... | 15.6-122 |
| 15.6.5.4B-11 | Inadvertent ADS – Accumulator-2 Injection Rate..... | 15.6-123 |
| 15.6.5.4B-12 | Inadvertent ADS – ADS-4 Integrated Discharge | 15.6-124 |
| 15.6.5.4B-13 | Inadvertent ADS – IRWST-1 Injection Rate..... | 15.6-125 |
| 15.6.5.4B-14 | Inadvertent ADS – IRWST-2 Injection Rate..... | 15.6-126 |
| 15.6.5.4B-15 | Inadvertent ADS – RCS System Inventory | 15.6-127 |
| 15.6.5.4B-16 | Inadvertent ADS – Core/Upper Plenum Mixture Level | 15.6-128 |
| 15.6.5.4B-17 | 2-Inch Cold Leg Break – RCS Pressure | 15.6-129 |
| 15.6.5.4B-18 | 2-Inch Cold Leg Break – Pressurizer Mixture Level..... | 15.6-130 |
| 15.6.5.4B-19 | 2-Inch Cold Leg Break – CMT-1 Mixture Level | 15.6-131 |
| 15.6.5.4B-20 | 2-Inch Cold Leg Break – CMT-2 Mixture Level | 15.6-132 |
| 15.6.5.4B-21 | 2-Inch Cold Leg Break – Downcomer Mixture Level..... | 15.6-133 |
| 15.6.5.4B-22 | 2-Inch Cold Leg Break – CMT-1 Injection Rate | 15.6-134 |
| 15.6.5.4B-23 | 2-Inch Cold Leg Break – CMT-2 Injection Rate | 15.6-135 |
| 15.6.5.4B-24 | 2-Inch Cold Leg Break – Accumulator-1 Injection Rate..... | 15.6-136 |
| 15.6.5.4B-25 | 2-Inch Cold Leg Break – Accumulator-2 Injection Rate..... | 15.6-137 |
| 15.6.5.4B-26 | 2-Inch Cold Leg Break – IRWST-1 Injection Rate | 15.6-138 |
| 15.6.5.4B-27 | 2-Inch Cold Leg Break – IRWST-2 Injection Rate | 15.6-139 |
| 15.6.5.4B-28 | 2-Inch Cold Leg Break – ADS-4 Liquid Discharge | 15.6-140 |
| 15.6.5.4B-29 | 2-Inch Cold Leg Break – RCS System Inventory..... | 15.6-141 |
| 15.6.5.4B-30 | 2-Inch Cold Leg Break – Core/Upper Plenum Mixture Level..... | 15.6-142 |
| 15.6.5.4B-31 | 2-Inch Cold Leg Break – ADS-4 Integrated Discharge | 15.6-143 |
| 15.6.5.4B-32 | 2-Inch Cold Leg Break – Liquid Break Discharge | 15.6-144 |
| 15.6.5.4B-33 | 2-Inch Cold Leg Break – Vapor Break Discharge..... | 15.6-145 |
| 15.6.5.4B-34 | 2-Inch Cold Leg Break – PRHR Heat Removal Rate..... | 15.6-146 |
| 15.6.5.4B-35 | 2-Inch Cold Leg Break – Integrated PRHR Heat Removal | 15.6-147 |
| 15.6.5.4B-36 | DEDVI – Vessel Side Liquid Break Discharge – 20 psi | 15.6-148 |
| 15.6.5.4B-37 | DEDVI – Vessel Side Vapor Break Discharge – 20 psi | 15.6-149 |
| 15.6.5.4B-38 | DEDVI – RCS Pressure – 20 psi..... | 15.6-150 |
| 15.6.5.4B-39 | DEDVI – Broken CMT Injection Rate – 20 psi | 15.6-151 |
| 15.6.5.4B-40 | DEDVI – Intact CMT Injection Rate – 20 psi | 15.6-152 |
| 15.6.5.4B-41 | DEDVI – Core/Upper Plenum Mixture Level – 20 psi | 15.6-153 |
| 15.6.5.4B-42 | DEDVI – Downcomer Mixture Level – 20 psi | 15.6-154 |
| 15.6.5.4B-43 | DEDVI – ADS 1-3 Vapor Discharge – 20 psi | 15.6-155 |
| 15.6.5.4B-44 | DEDVI – Core Exit Void Fraction – 20 psi | 15.6-156 |
| 15.6.5.4B-45 | DEDVI – Core Exit Liquid Flow Rate – 20 psi | 15.6-157 |
| 15.6.5.4B-46 | DEDVI – Core Exit Vapor Flow Rate – 20 psi | 15.6-158 |

LIST OF FIGURES (Cont.)

| <u>Figure No.</u> | <u>Title</u> | <u>Page</u> |
|-------------------|---|-------------|
| 15.6.5.4B-47 | DEDVI – Lower Plenum to Core Flow Rate – 20 psi | 15.6-159 |
| 15.6.5.4B-48 | DEDVI – ADS-4 Liquid Discharge – 20 psi..... | 15.6-160 |
| 15.6.5.4B-49 | DEDVI – ADS-4 Integrated Discharge – 20 psi | 15.6-161 |
| 15.6.5.4B-50 | DEDVI – Intact Accumulator Flow Rate – 20 psi..... | 15.6-162 |
| 15.6.5.4B-51 | DEDVI – Intact IRWST Injection Rate – 20 psi | 15.6-163 |
| 15.6.5.4B-52 | DEDVI – Intact CMT Mixture Level – 20 psi | 15.6-164 |
| 15.6.5.4B-53 | DEDVI – RCS System Inventory – 20 psi | 15.6-165 |
| 15.6.5.4B-54 | DEDVI – PRHR Heat Removal Rate – 20 psi | 15.6-166 |
| 15.6.5.4B-55 | DEDVI – Integrated PRHR Heat Removal – 20 psi..... | 15.6-167 |
| 15.6.5.4B-36A | DEDVI – Vessel Side Liquid Break Discharge – 14.7 psi | 15.6-168 |
| 15.6.5.4B-37A | DEDVI – Vessel Side Vapor Break Discharge – 14.7 psi..... | 15.6-169 |
| 15.6.5.4B-38A | DEDVI – RCS Pressure – 14.7 psi..... | 15.6-170 |
| 15.6.5.4B-39A | DEDVI – Broken CMT Injection Rate – 14.7 psi | 15.6-171 |
| 15.6.5.4B-40A | DEDVI – Intact CMT Injection Rate – 14.7 psi | 15.6-172 |
| 15.6.5.4B-41A | DEDVI – Core/Upper Plenum Mixture Level – 14.7 psi | 15.6-173 |
| 15.6.5.4B-42A | DEDVI – Downcomer Mixture Level – 14.7 psi | 15.6-174 |
| 15.6.5.4B-43A | DEDVI – ADS 1-3 Vapor Discharge – 14.7 psi | 15.6-175 |
| 15.6.5.4B-44A | DEDVI – Core Exit Void Fraction – 14.7 psi | 15.6-176 |
| 15.6.5.4B-45A | DEDVI – Core Exit Liquid Flow Rate – 14.7 psi | 15.6-177 |
| 15.6.5.4B-46A | DEDVI – Core Exit Vapor Flow Rate – 14.7 psi | 15.6-178 |
| 15.6.5.4B-47A | DEDVI – Lower Plenum to Core Flow Rate – 14.7 psi | 15.6-179 |
| 15.6.5.4B-48A | DEDVI – ADS-4 Liquid Discharge – 14.7 psi..... | 15.6-180 |
| 15.6.5.4B-49A | DEDVI – ADS-4 Integrated Discharge – 14.7 psi | 15.6-181 |
| 15.6.5.4B-50A | DEDVI – Intact Accumulator Flow Rate – 14.7 psi | 15.6-182 |
| 15.6.5.4B-51A | DEDVI – Intact IRWST Injection Rate – 14.7 psi | 15.6-183 |
| 15.6.5.4B-52A | DEDVI – Intact CMT Mixture Level – 14.7 psi | 15.6-184 |
| 15.6.5.4B-53A | DEDVI – RCS System Inventory – 14.7 psi | 15.6-185 |
| 15.6.5.4B-54A | DEDVI – PRHR Heat Removal Rate – 14.7 psi | 15.6-186 |
| 15.6.5.4B-55A | DEDVI – Integrated PRHR Heat Removal – 14.7 psi..... | 15.6-187 |
| 15.6.5.4B-56 | 10-Inch Cold Leg Break – RCS Pressure | 15.6-188 |
| 15.6.5.4B-57 | 10-Inch Cold Leg Break – Pressurizer Mixture Level..... | 15.6-189 |
| 15.6.5.4B-58 | 10-Inch Cold Leg Break – CMT-1 Mixture Level | 15.6-190 |
| 15.6.5.4B-59 | 10-Inch Cold Leg Break – CMT-2 Mixture Level | 15.6-191 |
| 15.6.5.4B-60 | 10-Inch Cold Leg Break – Downcomer Mixture Level..... | 15.6-192 |
| 15.6.5.4B-61 | 10-Inch Cold Leg Break – CMT-1 Injection Rate | 15.6-193 |
| 15.6.5.4B-62 | 10-Inch Cold Leg Break – CMT-2 Injection Rate | 15.6-194 |
| 15.6.5.4B-63 | 10-Inch Cold Leg Break – Accumulator-1 Injection Rate | 15.6-195 |
| 15.6.5.4B-64 | 10-Inch Cold Leg Break – Accumulator-2 Injection Rate | 15.6-196 |
| 15.6.5.4B-65 | 10-Inch Cold Leg Break – IRWST-1 Injection Rate | 15.6-197 |
| 15.6.5.4B-66 | 10-Inch Cold Leg Break – IRWST-2 Injection Rate | 15.6-198 |
| 15.6.5.4B-67 | 10-Inch Cold Leg Break – ADS-4 Liquid Discharge | 15.6-199 |
| 15.6.5.4B-68 | 10-Inch Cold Leg Break – RCS System Inventory..... | 15.6-200 |
| 15.6.5.4B-69 | 10-Inch Cold Leg Break – Core/Upper Plenum Mixture Level..... | 15.6-201 |

LIST OF FIGURES (Cont.)

| <u>Figure No.</u> | <u>Title</u> | <u>Page</u> |
|-------------------|---|-------------|
| 15.6.5.4B-70 | 10-Inch Cold Leg Break – Composite Core Mixture Level..... | 15.6-202 |
| 15.6.5.4B-71 | 10-Inch Cold Leg Break – Core Exit Liquid Flow | 15.6-203 |
| 15.6.5.4B-72 | 10-Inch Cold Leg Break – Core Exit Vapor Flow..... | 15.6-204 |
| 15.6.5.4B-73 | 10-Inch Cold Leg Break – Core Exit Void Fraction..... | 15.6-205 |
| 15.6.5.4B-74 | 10-Inch Cold Leg Break – ADS-4 Integrated Discharge | 15.6-206 |
| 15.6.5.4B-75 | 10-Inch Cold Leg Break – Liquid Break Discharge | 15.6-207 |
| 15.6.5.4B-76 | 10-Inch Cold Leg Break – Vapor Break Discharge..... | 15.6-208 |
| 15.6.5.4B-77 | 10-Inch Cold Leg Break – PRHR Heat Removal Rate..... | 15.6-209 |
| 15.6.5.4B-78 | 10-Inch Cold Leg Break – Integrated PRHR Heat Removal | 15.6-210 |
| 15.6.5.4B-79 | DEDVI – Downcomer Pressure Comparison | 15.6-211 |
| 15.6.5.4B-80 | DEDVI – Intact IRWST Injection Flow..... | 15.6-212 |
| 15.6.5.4B-81 | DEDVI – Intact DVI Line Injection Flow..... | 15.6-213 |
| 15.6.5.4B-82 | DEDVI – ADS-4 Integrated Liquid Discharge Comparison | 15.6-214 |
| 15.6.5.4B-83 | DEDVI – Upper Plenum Mixture Mass Comparison..... | 15.6-215 |
| 15.6.5.4B-84 | DEDVI – ADS-4 Integrated Vapor Discharge Comparison | 15.6-216 |
| 15.6.5.4B-85 | DEDVI – Downcomer Region Mass Comparison..... | 15.6-217 |
| 15.6.5.4B-86 | DEDVI – Core Region Mass Comparison..... | 15.6-218 |
| 15.6.5.4B-87 | DEDVI – Vessel Mixture Mass Comparison | 15.6-219 |
| 15.6.5.4B-88 | DEDVI – Core/Upper Plenum Mixture Level Comparison | 15.6-220 |
| 15.6.5.4B-89 | DEDVI – Core Collapsed Liquid Level Comparison | 15.6-221 |
| 15.6.5.4B-90 | DEDVI – Pressurizer Mixture Level Comparison..... | 15.6-222 |
| 15.6.5.4C-1 | Collapsed Level of Liquid in the Downcomer (DEDVI Case) | 15.6-223 |
| 15.6.5.4C-2 | Collapsed Level of Liquid over the Heated Length of the Fuel (DEDVI Case) | 15.6-224 |
| 15.6.5.4C-3 | Void Fraction in Core Hot Assembly Top Cell (DEDVI Case)..... | 15.6-225 |
| 15.6.5.4C-4 | Void Fraction in Core Hot Assembly Second from Top Cell (DEDVI Case) | 15.6-226 |
| 15.6.5.4C-5 | Collapsed Liquid Level in the Hot Leg of Pressurizer Loop (DEDVI Case)..... | 15.6-227 |
| 15.6.5.4C-6 | Vapor Rate out of the Core (DEDVI Case)..... | 15.6-228 |
| 15.6.5.4C-7 | Liquid Flow Rate out of the Core (DEDVI Case) | 15.6-229 |
| 15.6.5.4C-8 | Collapsed Liquid Level in the Upper Plenum (DEDVI Case)..... | 15.6-230 |
| 15.6.5.4C-9 | Mixture Flow Rate Through ADS Stage 4A Valves (DEDVI Case)..... | 15.6-231 |
| 15.6.5.4C-10 | Mixture Flow Rate Through ADS Stage 4B Valves (DEDVI Case) | 15.6-232 |
| 15.6.5.4C-11 | Upper Plenum Pressure (DEDVI Case)..... | 15.6-233 |
| 15.6.5.4C-12 | Peak Cladding Temperature (DEDVI Case)..... | 15.6-234 |
| 15.6.5.4C-13 | DVI-A Mixture Flow Rate (DEDVI Case)..... | 15.6-235 |
| 15.6.5.4C-14 | DVI-B Mixture Flow Rate (DEDVI Case) | 15.6-236 |
| 15.6.5.4C-1A | Collapsed Level of Liquid in the Downcomer (DEDVI Case) – 14.7 psi | 15.6-237 |
| 15.6.5.4C-2A | Collapsed Level of Liquid over the Heated Length of the Fuel (DEDVI Case) – 14.7 psi | 15.6-238 |
| 15.6.5.4C-3A | Void Fraction in Core Hot Assembly Top Cell (DEDVI Case) – 14.7 psi | 15.6-239 |
| 15.6.5.4C-4A | Void Fraction in Core Hot Assembly Second from Top Cell (DEDVI Case) – 14.7 psi..... | 15.6-240 |
| 15.6.5.4C-5A | Collapsed Liquid Level in the Hot Leg of Pressurizer Loop (DEDVI Case) – 14.7 psi | 15.6-241 |

LIST OF FIGURES (Cont.)

| <u>Figure No.</u> | <u>Title</u> | <u>Page</u> |
|-------------------|--|-------------|
| 15.6.5.4C-6A | Vapor Rate out of the Core (DEDVI Case) – 14.7 psi | 15.6-242 |
| 15.6.5.4C-7A | Liquid Flow Rate out of the Core (DEDVI Case) – 14.7 psi..... | 15.6-243 |
| 15.6.5.4C-8A | Collapsed Liquid Level in the Upper Plenum (DEDVI Case) – 14.7 psi | 15.6-244 |
| 15.6.5.4C-9A | Mixture Flow Rate Through ADS Stage 4A Valves (DEDVI Case) – 14.7 psi | 15.6-245 |
| 15.6.5.4C-10A | Mixture Flow Rate Through ADS Stage 4B Valves (DEDVI Case) – 14.7 psi | 15.6-246 |
| 15.6.5.4C-11A | Upper Plenum Pressure (DEDVI Case) – 14.7 psi | 15.6-247 |
| 15.6.5.4C-12A | Peak Cladding Temperature (DEDVI Case) – 14.7 psi | 15.6-248 |
| 15.6.5.4C-13A | DVI-A Mixture Flow Rate (DEDVI Case) – 14.7 psi | 15.6-249 |
| 15.6.5.4C-14A | DVI-B Mixture Flow Rate (DEDVI Case) – 14.7 psi | 15.6-250 |
| 15.6.5.4C-15 | Collapsed Level of Liquid in the Downcomer (Wall-to-Wall Floodup Case) – 14.7 psi | 15.6-251 |
| 15.6.5.4C-16 | Collapsed Level of Liquid Over the Heated Length of the Fuel (Wall-to-Wall Floodup Case) – 14.7 psi..... | 15.6-252 |
| 15.6.5.4C-17 | Void Fraction in Core Hot Assembly Top Cell (Wall-to-Wall Floodup Case) – 14.7 psi | 15.6-253 |
| 15.6.5.4C-18 | Void Fraction in Core Hot Assembly Second from Top Cell (Wall-to-Wall Floodup Case) – 14.7 psi | 15.6-254 |
| 15.6.5.4C-19 | Collapsed Liquid Level in the Hot Leg of Pressurizer Loop (Wall-to-Wall Floodup Case) – 14.7 psi..... | 15.6-255 |
| 15.6.5.4C-20 | Vapor Rate out of the Core (Wall-to-Wall Floodup Case) – 14.7 psi..... | 15.6-256 |
| 15.6.5.4C-21 | Liquid Flow Rate out of the Core (Wall-to-Wall Floodup Case) – 14.7 psi..... | 15.6-257 |
| 15.6.5.4C-22 | Collapsed Liquid Level in the Upper Plenum (Wall-to-Wall Floodup Case) – 14.7 psi | 15.6-258 |
| 15.6.5.4C-23 | Mixture Flow Rate Through ADS Stage 4A Valves (Wall-to-Wall Floodup Case) – 14.7 psi..... | 15.6-259 |
| 15.6.5.4C-24 | Mixture Flow Rate Through ADS Stage 4B Valves (Wall-to-Wall Floodup Case) – 14.7 psi..... | 15.6-260 |
| 15.6.5.4C-25 | Upper Plenum Pressure (Wall-to-Wall Floodup Case) – 14.7 psi | 15.6-261 |
| 15.6.5.4C-26 | Hot Rod Cladding Temperature Near Top of Core (Wall-to-Wall Floodup Case) – 14.7 psi..... | 15.6-262 |
| 15.6.5.4C-27 | DVI-A Mixture Flow Rate (Wall-to-Wall Floodup Case) – 14.7 psi..... | 15.6-263 |
| 15.6.5.4C-28 | DVI-B Mixture Flow Rate (Wall-to-Wall Floodup Case) – 14.7 psi | 15.6-264 |
| 15A-1 | Site Plan With Release and Intake Locations | 15A-18 |